

## Safer Room Unit

Storm Resistant  
Intrusion Resistant

### SPECIFICATIONS

<b>Frame</b>	14 GA. Cold-rolled steel; 5 3/4" Jamb Depth; KD
<b>Door</b>	14 GA. Cold-rolled steel; 1-13/16" thick 16 GA. Perimeter Channels 12 GA. Top and Bottom Flush Caps
<b>Bullet Resistant</b>	Level 1 – UL 752 tested
<b>Fire Rated</b>	Up to 3 Hours
<b>Paint</b>	Prime Painted
<b>Hinge Prep</b>	(3) 4 1/2" Standard Weight Butt Hinges
<b>Lock Prep</b>	(4) Cylindrical (161) Locks (2 1/8" Bore x 2 3/4" Back Set)
<b>Strike Prep</b>	(1) ASA 4 7/8" strike and (3) 2 3/4" Deadbolt Strikes
<b>Anchors</b>	Twist in Stud or Wire Masonry Anchors

### OPTIONS\*

<b>Door Types</b>	F, N, V and G
<b>Stainless Steel</b>	Type 316L or Type 304 ASTM A240 / A240M
<b>Galvanized Steel</b>	ASTM A653 / A653M – A60
<b>Bullet Resistant</b>	Up to Level 8
<b>Vision Panel</b>	DSM Proprietary
<b>Anchors</b>	Punch and Dimple with loose anchors
<b>Stock</b>	3068 and 3070
<b>Configurations</b>	Assembled with or without Hardware Welded Frame
<b>Customizations</b>	Size, Hardware and Features

\* Some options are mutually exclusive

### INDEPENDENT VERIFICATION AND QUALIFICATION TESTING

**Southwest Research Institute**  
UL 752

**UL / Intertek-Warnock Hersey**  
3 Hour Fire Resistant

DeanSteel Manufacturing Company  
931 S. Flores Street  
San Antonio, TX 78204

P 800.825.8271  
F 210.226.0913  
www.DeanSteel.com



MADE IN AMERICA  
AND VETERAN OWNED